

Intro. and Quick Selection

Incremental encoder

Absolute encoder

special position device

Accessories and Kits

Intro. and Quick Selection

Incremental encoder

Absolute encoder

special position device

Accessories and Kits

DAXB37

Small Blind Shaft Encoder

Features

- Small size, easy to install
- Standard CANopen protocol, SSI and biss protocol
- Up to 16 bit singleturn, 14 bit multiturn
- Suitable for instrument and other applications



CANopen SSI

Specifications

Electrical Specifications

Interface CAN open SSI/BISS

Supply Voltage 10-30VDC, 5VDC

Current Consumption 50mA 80mA

Output Code Binary Binary/Gray

Resolution 16 bit single turn (Max.),
14 bit multiturn (Max.)

Output speed 1MBit/s 0.1-2 MBit/s

Criterion DSP406, Class 1 Class2 RS422

linearity 1LSB

Mechanical Specifications

Maximum speed 8000rpm

Shaft load Axial 20N Radial 40N

Starting Torque <0.02Nm

Shock Resistance EN 60068-2-27 1000m/s² 6ms

Vibration Resistance EN 60068-2-6 100m/s² 55....2000HZ


Operating Temperature -40°C to +80°C

Protection Class IP65/IP67 (option)

Material stainless steel (316L)

Weight 150g

Dimension (Installation flanges, hole positions, etc. shall be subject to the order confirmation)



unit: mm

D=6, on request

Connection

SSI 3A/3R

GND white
VCC brown
CLCOK+ green
CLOCK- yellow
DATE+ grey
DATE- pink
ZERO blue
DIR red

CANopen 3A/3R

GND white
VCC brown
CAN_GROUND green
CAN_LOW(-) yellow
CAN_HIGH(+) grey

Ordering Code

Example: DASB370012E06SB3A
37single turn 12 bit resolution SSI binary blind shaft encoder, power voltage 10-30V DC, radial straight out cable

DAXB37	resolution	power	shaft	output	connection
DASB=ST	1212=12 MT	A=5VDC	06=6mm	SB=SSI binary	3A=axial output
DAMB=MT	12 ST	E=10-30VDC	XX=custom-made	SG=SSI gray	3R=radial output
	1213=12 MT			CO=CANopen	
	13 ST				
	1214=12 MT				
	14 ST				
	1216=12 MT				
	16 ST				
	0012=12 ST				
	0016=16 ST				
	custom-made				