

Intro. and Quick Selection

Incremental encoder

Absolute encoder

special position device

Accessories and Kits

Intro. and Quick Selection

Incremental encoder

Absolute encoder

special position device

Accessories and Kits

EAXB58

DP Blind Shaft Encoder

Features

- With optical coupler isolation standard PROFIBUS-DP interface
- Terminal resistance, address and so on can be set (dip switch)
- Up to 21 bitsingleturn,14bitmultiturn
- Suitable for group control with industrial bus and other applications



Specifications


Electrical Specifications

Interface	Profibus DP
Supply Voltage	10-30VDC
Current Consumption	200mA
Output Code	Binary
Resolution	21 bit single turn (Max.), 14 bit multiturn (Max.)
Output speed	0.001-12MBit/s
Criterion	DPV0,DPV1 and DPV2 Class 2
linearity	1LSB

Mechanical Specifications

Maximum speed	12000rpm
Shaft load	Axial 50N Radial 100N
Starting Torque	<0.05Nm
Shock Resistance	EN 60068-2-27 1000m/s² 6ms
Vibration Resistance	EN 60068-2-8 100m/s², 55 ... 2000 Hz
Operating Temperature	-40°C to +80°C
Protection Class	IP66
Material	aluminium alloy
Weight	300g

Dimension (Installation flanges, hole positions, etc. shall be subject to the order confirmation)



unit: mm

D=6,10,on request

Connection

DP	Z
BUS IN(B)	5
BUS IN(A)	6
BUS IN(0 V)	2
BUS IN(+ V)	1
BUS OUT(B)	7
BUS OUT(A)	8
BUS OUT(0 V)	4
BUS OUT(+ V)	3

Ordering Code

Example: EASB580012E06DPZ
58single turn 12 bit resolution profibus blind shaft encoder, power voltage 10-30V DC, aperture 6mm, terminal box

EAXB58	resolution	power	shaft	output	connection
EASB=ST	1212=12 MT	E=10-30VDC	06=6mm	DP=profibus	Z=tenminal
EAMB=MT	12 ST		10=10mm		3xPG9
	1214=12 MT		XX=custom-made		
	14 ST				
	1021=10 MT				
	21 ST				
	1220=12 MT				
	20 ST				
	1418=14 MT				
	18 ST				
	0012=12 ST				
	0021=21 ST				
	custom-made				